





Dragon is intended to transport different types of oxy-fuel cutting torches with a grip diameter 28-35 mm (1-1/8" to 1-3/8") to perform machine quality cutting and beveling processes in a variety of applications.



High speed plasma cutting and beveling is available by means of Dragon HS




Primary features and benefits:

- State-of-the-art, digitally controlled track torch
- Cutting and beveling up to 45° (also parallel by means of 2 torches)
- Quick clamping torch holder for torch diameter from 28 mm to 35 mm
- Advanced speed control system with implemented digital PID regulator
- LED display with readout of actual and set speed, and report messages
- Rigid heat-proof design
- 2-wheel drive with auto braking drive unit
- · Quick drive release switch for easy re-positioning
- Runs on a rail or directly on a workpiece
- Connectable rails to form various lengths
- Wide assortment of optional accessories for variety of applications, like machine barrel torch holders, manifolds, circle cutting attachment etc.

TECHNICAL SPECIFICATIONS			
	Dragon	Dragon HS	
Voltage	~ 115–230 V, 50–60 Hz	~ 115-230 V, 50-60 Hz	
Power	20 W	20 W	
Operating position	horizontal	horizontal	
Torch diameter	28-35 mm (1.10-1.38")	28-35 mm (1.10-1.38")	
Ground clearance	8 mm (0.31")	8 mm (0.31")	
Speed	0-150 cm/min (0-59 in/min)	10-300 cm/min (4-118 in/min)	
Weight	16.8 kg (37.0 lbs)	16.8 kg (37.0 lbs)	

Dimensions:

















Standard accessories for both Dragon and Dragon HS



540 mm (21") Geared Rack RAM-0525-07-00-00-0



Counterweight 1.3 kg (2.9 lbs) PWG-0475-09-00-00-0



Standard Torch Holder with angle adjustment UCW-0475-28-00-00-0



Power cord 3 m (9,7 ft)

Optional accessories for both Dragon and Dragon HS



Track Assembly 1800 mm (70,9") "V" Groove Center Line 152 mm (6") TRO-0475-13-00-00-0



Magnetic Unit ZSP-0475-92-00-00-0



Heat-resistant magnetic unit ZSP-0475-93-00-00-0



Lightweight Magnetic Unit MST-0677-00-00-00-0



Magnetic Narrow Unit with hexagon PDS-0582-10-00-02-0



Vacuum Modular Unit MST-0541-10-02-00-0



Standard Torch Holder 28-35 mm (1.10"-1.38") ZCS-0475-28-10-00-0



Precise Torch Holder with angle and height adjustment UCW-0475-08-00-00-0



Geared Rack RAM-0475-23-00-00-0



Large Counterweight 2,6 kg (5,7lbs) PWG-0475-10-00-00-0



Slide Rack Holder UCW-0475-15-00-00-1



Cable Anchor PDT-0475-34-00-00-0





Circle Cutting Attachment CYR-0475-22-00-00-0



Roller Support PDT-0475-26-00-00-0





Heat Protection Shield (left) OSL-0475-54-00-00-0



Heat Protection Shield (right) OSL-0475-55-00-00-0






Heat Protection Shield (bottom) OSL-0475-53-00-00-0

Optional accessories for Oxy-fuel

Gas Manifold	type	Metric	Imperial
Manifold 2x2		RZD-0475-64-00-00-0	RZD-0475-68-00-00-0
Manifold 2x3		RZD-0475-63-00-00-0	RZD-0475-67-00-00-0
Manifold 3/3		RZD-0475-74-00-00-0	RZD-0475-73-00-00-0
Manifold 2x2 cut-off valve	with	RZD-0475-65-00-00-0	RZD-0475-70-00-00-0
Manifold 2/3 cut-off valve	with	RZD-0475-66-00-00-0	RZD-0475-69-00-00-0
Manifold 3/3 cut-off valve	with	RZD-0475-72-00-00-0	RZD-0475-71-00-00-0







Machine Barrel Torch Holder Ø 30 mm (1.18") UCW-0475-61-00-00-0

Machine Barrel Torch Holder Ø 35 mm (1.38") UCW-0475-29-00-00-1



Precise Machine Torch Holder Ø 30 mm (1.18") UCW-0475-59-00-00-0

Precise Machine Torch Holder Ø 35 mm (1.38") UCW-0475-42-00-00-1

Optional accessories for Plasma (Dragon HS)



Plasma Arc Ignition ZSP-0475-58-00-00-0



Plasma Arc Ignition Cable





More information available at www.promotech.eu



You

American Welding Society Supporting Company Member

Your local dealer:

tel. (+48 85) 678 34 05, fax (+48 85) 662 78 77 marketing@promotech.eu www.promotech.eu